

# BUBBLER NOZZLES







Deliver a consistent flow regardless of inlet pressure with pressure-compensating bubbler nozzles.

## KEY BENEFITS

- Pressure-compensating for constant water flow at any pressure
- Designed for deep watering of planted areas
- Nozzle threaded for use with Pro-Spray
- Warranty period: 2 years

NOZZLES

### MULTI-STREAM BUBBLER PERFORMANCE DATA

Arc	Model	Flow GPM	Radius ft.
	MSBN-25Q	0.25	1.0
	MSBN-50Q	0.50	1.5
	MSBN-50H	0.50	1.0
	MSBN-10H	1.00	1.5
	MSBN-10F	1.00	1.0
	MSBN-20F	2.00	1.5

Multi-Stream Bubbler



### MULTI-STREAM BUBBLER NOZZLES



**MSBN-25Q**  
Flow: 0.25 GPM



**MSBN-50Q/50H**  
Flow: 0.50 GPM



**MSBN-10H/10F**  
Flow: 1.0 GPM



**MSBN-20F**  
Flow: 2.0 GPM

#### Notes:





Typical spacing 2' to 4'. Flows shown for pressures between 15 and 70 PSI.



#### MSBN Installed on PROS-04

Combining Hunter Bubbler Nozzles with the Pro-Spray provides the watering precision of pressure-compensating bubblers paired with the benefit of retracting the nozzle out of sight.

### PCN PERFORMANCE DATA

Model	Flow GPM	Pattern Type
 25	0.25	Trickle
 50	0.50	Trickle
 10	1.00	Umbrella
 20	2.00	Umbrella

PCN



### PCN BUBBLER NOZZLES



**PCN-25**  
Flow: 0.25 GPM



**PCN-50**  
Flow: 0.50 GPM



**PCN-10**  
Flow: 1.0 GPM




**PCN-20**  
Flow: 2.0 GPM

#### Notes:

Typical spacing 2' to 4'. Flows shown for pressures between 15 and 70 PSI.

### 5-CST-B BUBBLER NOZZLE PERFORMANCE DATA

Pressure (PSI)	Radius (ft.)	Flow (GPM)
 20	5	0.30
25	5	0.32
30	5	0.38
35	5	0.40
40	5	0.42

5-CST-B



### DUAL-STREAM BUBBLER NOZZLE



**5-CST-B**